



# FOXGOLDEN GROUP LIMITED

No.57,Shuitian Fourth Industry,Zhulongtian Road,Shiyan Town,Baoan District,Shenzhen City, China

Tel: +86 0755 84253360 , MP: +86 13699752576, Fax: 84253359

E-mail:salesb@foxgolden.cn

Web:www.foxgolden.com

**FOXGOLDEN**

## Quotation List

Invoice:FOXLYQ20163001	Date: 2016-06-30
Buyer: NWNetworks	Seller: FOXGOLDEN GROUP LIMITED
Add.:Street: tulpenweg 14 ,City: Ried im Innkreis, City code: 4910, Country: Austria	Add.: No.57,Shuitian Fourth Industry,Zhulongtian Road,Shiyan Town,Baoan District,Shenzhen City, China
Tel:	Tel:+86 13699752576
Contact:Wilhelm Neulentner	Contact: Mary Li

### Products: P8 outdoor Full Color LED Displays

#### Quotation

No.	Items	Description	Quantity	Unit	Unit Price (USD)	Total Price (USD)	
1	Display Body	Screen Size(W*H)	6,3	sq m			
		Module Size(W*H)					3.072*2.048 m
		Cabinet Size(W*H)					256mm*128mm
		Cabinet Material					1024*1024mm
2	Control System	1 sending card	1	pcs			
		2 Receiving card	6	pcs			
		3 Humidity&Tem. sensor	1	set			
3	Spare Part	1 P8 LED module	10	pcs			
		2 P8 LED module	2	pcs	0,00	free	
		3 power supply	2	pcs	0,00	free	
		4 installation manul +CAD guide drawing	1+1	pcs	0,00	free	
		5 software	1	pcs	0,00	free	
		6 power cable+data cable	15+15	pcs	0,00	free	
		7 LED lamps , ICs	20+20	pcs	0,00	free	
4	Packaging	1 Anti-shaking wooden case					
5	Bank fee	1 Buyer and seller both should bear half bank fee					
Total EXW Price							
5 Say Total: <b>Five Thousand Two Hundred and Nineteen USD Dollars Only.</b>							
6	Shipping	1 By air from Shenzhen ,China to LINZ,Austria					
		2 By DHL from Shenzhen ,China to Austria					

#### Technical Specification

1	Pixel	Package Mode LED	SMD3535
		Pixel Configuration	SMD3IN1
		Wave length (nm )	R:626-628,G:518*520,B:466-468
2	Module	Module size (mm )	256*128
		Module Pixel(dot )	32*16
3	Cabinet	Module quantity in a cabinet	32 pcs ---- 4 (W)*8 (H)
		Unit box size (mm)	1024*1024*120
		Pixel resolution for a cabinet (dots )	128(W)*128 (H)= 16384
		cabinet material	steel
		Weight ( kg/cabinet )	50



4	Screen	Total Cabinets Quantities for the whole screen ( pcs )	3 (W) * 2 (H) = 6
		Total Pixel Resolution on the whole screen (dots )	384 * 256 = 98304
		Final screen size ( m2 )	3.072 m (W)*2.048 m(H) = 6.3
5	Control System	Sending card	1 pcs
		Receiving card	6 pcs
		Humidity&Tem. sensor	1 set
6	Packaging	Packaging Way	6 cabinets in 1 case
		Packaging box material	wooden
		Packaging box quantity	1 pcs
7	Electricity parameter	pixel density ( dots/m2 )	10000
		white balance brightness (cd/m2)	6000-8500
		LED driving method	1 / 4 scanning
		Best Viewing Distance	8 -250 m
		LED lamp	Eplstar
		IC	5024 Energing saving IC
		Working temperature ( °C )	- 20~ + 60
		screen life time ( hours)	≧ 100, 000
		whole display flatness	less than 1 mm juncture
		Maintenance way	back maintenance
		Power supply	2 2 0 V
		power consumption (w/m2)	≤ 1100
		Input Voltage	88-132VAC/176-264 VAC;47-63Hz
		<b>Brightness Control</b>	Manual 256 level & Auto. 8 level
		Dot Defects Rate	≤ 0.0001
		Operating Temp.& RH	- 20°C~65°C / 20%~90%RH
		Storage Temp. & RH	- 40°C~85°C / 10%~95%RH
Input Signal	RF,S-Video,RGB,RGBHV, YUV,YC,COMPOSITION,etc.		
Communication Cable	CAT5(≤100m); Optical Fiber(500m-15000m)		

